

The 46 Series Casters are heat treated and recommended in medium to medium heavy duty applications. These are the mainstay in industrial caster applications.



46-UPR-0620-S-SL-ICWB

FEATURES	
Swivel Section	Cold formed top plate, yoke and button are all heat treated to prevent brinelling, improve swivel action and increase service life. Load and thrust bearings are hardened and ground and rotate on hardened raceways. Top plate and legs are 1/4" steel, legs formed for increased strength and continuously welded to yoke. All swivel sections are equipped with a lubrication fitting for field maintenance. RWM lubricates all swivel sections prior to shipment. Notched yokes are standard.
Kingpin	5/8" diameter rivet hydraulically compressed to increase strength of swivel section as compared to staking
Axle	1/2" diameter drilled axle with lubrication fitting provided on all casters to improve ease of lubrication
Finish	Zinc plated to protect from corrosion
Wheels	A wide variety of 3-1/4" through 8" diameters available with either roller, ball bearing, celcon or plain bearings
Mounting Plate Size	4" x 4-1/2" x 1/4" Bolt Hole Spacing 2-5/8" x 3-5/8", slotted to 3" x 3" Mounting Bolt Diameter 3/8"

Wheel Dia.	Wheel Width	Wheel Type	lbs. Capacity	Overall Height	Swivel Caster Model Number			Swivel Lead	Approx Weight
					Caged, Straight Roller Bearing	Flanged, Sealed Precision, 1 pc. Ball Bearing	Plain, Oilite, Celcon Bearing		
3-1/4"	2"	Durastan	400	5-1/4"	46-DUR-3220-S		46-DUC-3220-S	1-7/16"	6.7
		Urethane on Iron	450		46-UIR-3220-S	46-UIB-3220-S	46-UIC-3220-S		5.0
4"	1-1/2"	Forged Steel	1200	5-5/8"	46-FSR-0415-S		46-FSC-0415-S	1-3/8"	7.0
4"	2"	Cast Iron	800	5-5/8"	46-CIR-0420-S	46-CIB-0420-S	46-CIC-0420-S	1-3/8"	6.5
		Durastan	800		46-DUR-0420-S	46-DUB-0420-S	46-DUC-0420-S		5.2
		GT	1050						5.2
		High Temp Nylon	800		46-HNR-0420-S				5.2
		Nylatron HD	1200			46-NYB-0420-S			5.7
		Performance TPR	350		46-RPR-0420-S	46-RPB-0420-S	46-RPC-0420-S		5.3
		Polyolefin	500		46-POR-0420-S	46-POB-0420-S	46-POC-0420-S		4.8
		Rubber on Aluminum	525			46-RAB-0420-S-EHT			7.4
		Rubber on Iron	350		46-RIR-0420-S		46-RIC-0420-S		7.5
		Solid Urethane	700			46-MUB-0420-S			5.5
		Urethane on Aluminum	700		46-UAR-0420-S		46-UAC-0420-S		5.0
		Urethane on Iron	700		46-UIR-0420-S		46-UIC-0420-S		6.6
		Urethane Polypropylene	600		46-UPR-0420-S	46-UPB-0420-S	46-UPC-0420-S		5.3
		V-Groove Iron	800		46-VIR-0420-S		46-VIC-0420-S		7.6
		Signature	400		46-SWR-0420-S	46-SWB-0420-S	46-SWC-0420-S		5.5
		Pinnacle	800		46-PNR-0420-S	46-PNB-0420-S	46-PNC-0420-S		5.2
5"	2"	Cast Iron	1000	6-1/2"	46-CIR-0520-S	46-CIB-0520-S	46-CIC-0520-S	1-11/16"	7.8
		Durastan	1000		46-DUR-0520-S	46-DUB-0520-S	46-DUC-0520-S		5.4
		GT	1200						5.4
		Forged Steel	1200		46-FSR-0520-S		46-FSC-0520-S		8.1
		High Temp Nylon	1000		46-HNR-0520-S				5.4
		Nylatron HD	1200			46-NYB-0520-S			5.9
		Performance TPR	375		46-RPR-0520-S	46-RPB-0520-S	46-RPC-0520-S		5.3
		Polyolefin	650		46-POR-0520-S	46-POB-0520-S	46-POC-0520-S		4.6
		Rubber on Aluminum	600			46-RAB-0520-S-EHT			7.5
		Rubber on Iron	400		46-RIR-0520-S		46-RIC-0520-S		7.6
		Solid Urethane	1000			46-MUB-0520-S			5.7
		Urethane on Aluminum	1050		46-UAR-0520-S		46-UAC-0520-S		5.5
		Urethane on Iron	1050		46-UIR-0520-S		46-UIC-0520-S		7.7
		Urethane Polypropylene	750		46-UPR-0520-S	46-UPB-0520-S	46-UPC-0520-S		5.3
		V-Groove Iron	800		46-VIR-0520-S		46-VIC-0520-S		9.9
		Signature	500		46-SWR-0520-S	46-SWB-0520-S	46-SWC-0520-S		5.7
Pinnacle	1000	46-PNR-0520-S	46-PNB-0520-S	46-PNC-0520-S	5.6				
6"	2"	Cast Iron	1200	7-1/2"	46-CIR-0620-S	46-CIB-0620-S	46-CIC-0620-S	1-3/4"	9.1
		Durastan	1200		46-DUR-0620-S	46-DUB-0620-S	46-DUC-0620-S		6.3
		GT	1200						6.3
		Forged Steel	1200		46-FSR-0620-S		46-FSC-0620-S		10.0
		High Temp Nylon	1200		46-HNR-0620-S				6.3
		Omega	1000		46-UOR-0620-S	46-UOB-0620-S			8.8
		Performance TPR	525		46-RPR-0620-S	46-RPB-0620-S	46-RPC-0620-S		5.7
		Polyolefin	700		46-POR-0620-S	46-POB-0620-S	46-POC-0620-S		5.0
		Rubber on Aluminum	615			46-RAB-0620-S-EHT			7.8
		Rubber on Iron	410		46-RIR-0620-S		46-RIC-0620-S		7.8
		Solid Urethane	1200			46-MUB-0620-S			6.4
		Urethane on Aluminum	1200		46-UAR-0620-S		46-UAC-0620-S		6.1
		Urethane on Iron	1200		46-UIR-0620-S	46-UIB-0620-S	46-UIC-0620-S		8.8
		Urethane Polypropylene	900		46-UPR-0620-S	46-UPB-0620-S	46-UPC-0620-S		5.7
		V-Groove Iron	1000		46-VIR-0620-S		46-VIC-0620-S		10.9
		Signature	600		46-SWR-0620-S	46-SWB-0620-S	46-SWC-0620-S		6.4
Pinnacle	1200	46-PNR-0620-S	46-PNB-0620-S	46-PNC-0620-S	6.2				
Torus	1200		46-UAB-0621-S		6.1				
8"	2"	Cast Iron	1200	9-1/2"	46-CIR-0820-S	46-CIB-0820-S	46-CIC-0820-S	2-1/4"	13.3
		Durastan	1200		46-DUR-0820-S	46-DUB-0820-S	46-DUC-0820-S		7.7
		GT	1200						7.7
		Omega	1200		46-UOR-0820-S	46-UOB-0820-S			12.1
		Performance TPR	600		46-RPR-0820-S	46-RPB-0820-S	46-RPC-0820-S		7.1
		Polyolefin	800		46-POR-0820-S	46-POB-0820-S	46-POC-0820-S		5.8
		Rubber on Aluminum	750			46-RAB-0820-S-EHT			10.1
		Rubber on Iron	500		46-RIR-0820-S		46-RIC-0820-S		10.1
		Solid Urethane	1200			46-MUB-0820-S			7.1
		Urethane on Aluminum	1200		46-UAR-0820-S		46-UAC-0820-S		7.3
		Urethane on Iron	1200		46-UIR-0820-S	46-UIB-0820-S	46-UIC-0820-S		12.1
		Urethane Polypropylene	1000		46-UPR-0820-S	46-UPB-0820-S	46-UPC-0820-S		7.7
		V-Groove Iron	1050		46-VIR-0820-S		46-VIC-0820-S		15.3
		Signature	700		46-SWR-0820-S	46-SWB-0820-S	46-SWC-0820-S		7.1
		Pinnacle	1200		46-PNR-0820-S	46-PNB-0820-S	46-PNC-0620-S		6.9
		Torus	1200			46-UAB-0821-S			7.3

OPTIONAL MOUNTING PLATES			
Opt. Top Plate No.	Mounting Plate	Bolt Hole Spacing	Bolt Size
41ST / 41RT	4" x 5"	2-5/8" x 3-5/8" slotted to 3" x 4"	3/8"
42ST / 42RT	4-1/2" x 6-1/2"	2-7/16" x 4-15/16" slotted to 3-3/8" x 5-1/4"	1/2"
43ST / 43RT	5" x 5-1/2"	4-1/8" x 4-1/2"	3/8"

OPTIONAL OVERALL HEIGHTS	
Wheel Diameter	Overall Height
4"	5-1/4"
5"	6-1/8"
5"	6-3/8"
6"	7-1/4"
6"	7-3/8"
6"	7-3/4"
8"	9-1/4"
8"	9-3/4"

OPTIONS	
DSL	Demountable Swivel Lock
HT	High Temperature Lubrication
ICWB	Installable Face Contact Brake
LT	Low Temperature Lubrication
KB	Nut and Bolt Kingpin
SL	Swivel Lock
SR	Sealed Swivel Raceway
TG	Thread Guards
WB	Field Installable Side Wheel Brake on 4" & Larger, Roller Bearings Only
WS	Wheel Seals
WWB	Wrap Around Wheel Brake Roller Bearing Only
FCNB	Face Contact Nylon Brake
FCNTLB	Face Contact Nylon Total Lock Brake
FCSTLB	Face Contact Steel Total Lock Brake
FOSL	Foot Operated Swivel Lock

To order a rigid caster, change the "S" to "R" in the model number. For example: "46-DUR-3220-R". To order a rig only, omit the blue letters. For example: "46-3220-S". Dimensions shown are nominal. If precise dimensions are required, consult your RWM representative. For approximate weight of our rigid casters, deduct 0.9 pounds per item.

NSF
COMPONENT

Available NSF Products:
All casters except those with cast iron, soft rubber, rubber on iron, rubber on aluminum, Omega, forged steel, urethane on aluminum, urethane on iron or V-groove wheels. The following options are also not available: DSL, HT, LT, KB, SL, SR, WS, TG. Add "-N" to the end of the model number to specify an NSF approved caster. For example: 46-DUR-0620-S-N.

UP TO 1,200 POUND CAPACITY